


CuraSlide™ Safety IV Catheter

PTFE (polytetrafluoroethylene) High tensile strength catheter material








product specifications

- Slide style needle retraction
- Ground stainless-steel needle
- Straight hub
- Disposable
- Non-pyrogenic
- Not made with natural rubber latex
- Not made with DEHP
- ISO 10555-5 compliant color-coding
- Needlestick Safety and Prevention Act (NSPA) of 2000 compliant



ISO 80369-7:2021 Compliant

ordering information

Color	Item #	Gauge and Length	Catheter ID (mm)	Catheter OD (mm)	Gravity Flow Rate (mL/min)	Qty
	1612-84110	14G x 1.25"	1.6mm	2.1mm	270mL/min	1/ea, 50/bx, 200/case
	1612-84120	16G x 1.25"	1.38mm	1.8mm	200mL/min	1/ea, 50/bx, 200/case
	1612-84130	18G x 1.25"	0.95mm	1.3mm	85mL/min	1/ea, 50/bx, 200/case
	1612-84140	20G x 1.25"	0.78mm	1.1mm	55mL/min	1/ea, 50/bx, 200/case
	1612-84145	20G x 1"	0.78mm	1.1mm	55mL/min	1/ea, 50/bx, 200/case
	1612-84150	22G x 1"	0.62mm	0.9mm	33mL/min	1/ea, 50/bx, 200/case
	1612-84160	24G x 0.75"	0.49mm	0.7mm	18mL/min	1/ea, 50/bx, 200/case

